



code: 103

EXCELLENCE 15W-40

Multigrade motor oil

Specifications:

ACEA A3/B4; API SN/CF

Suitable for use in applications requiring: VW 501 01, VW 505 00; MB 229.1 ; PSA B712295

Product Features:

- EXCELLENCE SAE 15W-40 is a multi-grade lubricant manufactured from high quality mineral oils and a high performance additive system and designed specifically to meet wide range of new or old generation car engines and light industrial vehicle suitable for gasoline and diesel with or without turbochargers. It has perfect lubricating properties and viscosity stability combined with deposit and wear control.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

Volume / weight:

- 1L
- 5L
- 20L
- 200L

Updated: 04/11/2023 (15:30)

Typical Inspection Data:

Density @ 20°C	0.862 g/cm ³
Viscosity @ 100°C	14.6 cSt
Viscosity Index	158
Flash Point	231°C
Pour Point	-29°C
Colour	Yellow Brown